



ACTUAL SIZE

- B3** PRODUCTION LEAK TEST: WITH THE 'VAC' SIDE OF VALVE PRESSURIZED TO 3 PSI-LEAK RATE TO BE LESS THAN OR EQUAL TO 2 SCCM.
- A1** CHECK VALVE SPECIFICATION:
- 1.OPERATING TEMPERATURE RANGE: -20° F - 250° F
 - 2. FUNCTIONAL OPERATING PRESSURES BETWEEN 0.5 PSI AND 15 PSI.

FORWARD FLOW WITH 5 PSI g APPLIED TO INLET TO BE ¹²--- CFH MINIMUM.

B3	ADDED PROD LEAK TEST NOTE	080328	CHK CHABA	BRYIR	KATOI
B2	16/14 WAS 15				
B1	17.8/15.8 WAS 16.8				
A2	Ø19 WAS Ø19.1/19.0	970725			
A1	ADDED SPECIFICATION 1 & 2	-		-	-
REV	DESCRIPTION	DATE	DRAWN CHECKED	ENG. APPROVAL	AQP

WAS: LAYOUT NUMBER:



DO NOT SCALE NUMBER OF DECIMAL PLACES DOES NOT IMPLY A TOLERANCE

DRAWN BY DAB	CHECKED BY MBL	DESIGNED BY MTV	SCALE 4:1
DATE 890117	DATE 890117	DATE 890117	DRAWING SIZE C
PRD ENGINEER -	MFG ENGINEER -	QC -	TOOL ENGINEER -
DATE -	DATE -	DATE -	DATE -
CUSTOMER NUMBER VARIOUS	DATE -	REV -	

DRAWING TITLE 1/8" CHECK VALVE ASSEMBLY			MODEL REV	DRAWING REV B	SHEET 1/1
			DRAWING NUMBER A446		

THIS DRAWING CONFORMS TO ASME Y14.5 - 1994	
THIRD ANGLE PROJECTION	
UNLESS OTHERWISE SPECIFIED	
MAX COMBINED PARTING LINE FLASH AND MISMATCH TO BE	
SURFACE FINISH EXTERIOR INTERIOR	

THE DATA, DRAWINGS, AND INFORMATION CONTAINED ON THIS DOCUMENT IS CONFIDENTIAL AND THE SOLE PROPERTY OF MPC INC. AND MAY NOT BE REPRODUCED, USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION OF AN OFFICER OF MPC INC.	
WEIGHT (kg) -CAD 0.002	METRIC LINEAR DIMENSIONS ARE MM UNLESS NOTED
VOLUME (MM³) -CAD	